Product Specifications

COMMSCOPE®

POWERED BY ANDREW®

SGL4-15B4

SureGround® Grounding Kit for 1/2 in corrugated coaxial cable

OBSOLETE

Replaced By:

SG12-12B2U	SureGround® Grounding Kit for 1/2 in coaxial cable
SG12-15B4	SureGround® Grounding Kit for 1/2 in coaxial cable

Dimensions

Nominal Size	1/2 in
Bonding Conductor Length	1524.0 mm | 60 in
Cable Jacketing Removal Length, maximum	59.1 mm | 2.3 in
Cable Jacketing Removal Length, minimum	55.9 mm | 2.2 in
Compatible Diameter, maximum	16.510 mm | 0.650 in
Compatible Diameter, minimum	15.494 mm | 0.610 in

Electrical Specifications

Current Handling	Tested to withstand 100,000 amps peak current surge
Current Handling Test Method	MIL-STD-1757
Grounding, Bonding and Shielding Test Method	MIL-STD-188-124A
Lightning Protection Test Method	IEC 1024-1

General Specifications

Cable Type	Corrugated
Grounding Kit Type	SureGround™ Grounding Kits
Brand	SureGround™
Color	Black
Bonding Conductor Material	Copper
Bonding Conductor Wire Size	6 gauge
Bonding Conductor Jacketing Material	PE
Grounding Strap Material	Copper
Includes	Grounding kit | Hardware | Lug | One roll of 2 in PVC tape | One roll of 24 in butyl rubber tape
Locking Bail Material	Stainless steel
Lug Attachment	Field attached
Lug Type	Two-hole lug
Package Quantity	1
Rivet Material	Copper
Weatherproofing Method	Butyl and electric tape

©2013 CommScope, Inc. All rights reserved. All trademarks identified by ® or ™ are registered trademarks, respectively, of CommScope.
All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: July 26, 2013

Product Specifications

SGL4-15B4

Mechanical Specifications

Blowing Rain Test Method	MIL-STD-810, Method 506
Corrosion Test Method	MIL-STD-1344, Method 1001
Freezing Rain/Icing Test Method	MIL-STD-810, Method 521
Humidity Test Method	MIL-STD-1344, Method 1002
Immersion Test Method	IEC 60529:2001, IP68
Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
Storage Temperature	-40 °C to +80 °C (-40 °F to +176 °F)
Thread Size	3/8 in
UV Resistance Test Method	MIL-STD-810, Method 505
Vibration Test Method	MIL-STD-202, Method 214

Packed Dimensions

Height	269.2 mm | 10.6 in
Length	266.7 mm | 10.5 in
Shipping Weight	0.81 kg | 1.79 lb
Width	56.9 mm | 2.2 in

Included Products

9905-71 — Black 2 in PVC Tape, 20 ft

42615-10 — Butyl Rubber Tape, 24 in

* Footnotes

Grounding, Bonding and Shielding Test Method	Military Standard for Grounding, Bonding, and Shielding: Bond Resistance Requirement of a Maximum dc resistance of 0.001 ohm
Lightning Protection Test Method	Protection Against Lightning Electromagnetic Impulse, Table 1—Protection Level III–IV, 1995-02

©2013 CommScope, Inc. All rights reserved. All trademarks identified by ® or ™ are registered trademarks, respectively, of CommScope.
All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: July 26, 2013