

STAKE (4) PLACES .008/.012 DEEP
6 LBS. MIN. RETENTION

.250-36UNS-2A

CONTACT .000/.005
INSULATOR .000/.005

.562 ACROSS
FLATS

.625-24UNEF-2B

STAMP 'AMPHENDL 901-B2501-510'
IN .060 HIGH DEPRESSED CHARACTERS

1.35 MAX./1.33 NOM.

.038 REF

- | | |
|---|---|
| H:\BDB\SMA\901B.VASSY\25015100 | |
| UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE:
2 PLACE DECIMAL
±.015 (0,381 mm)
±.005 (0,127 mm) | MATERIAL |
| NOTE: - These drawings, specifications, or other data (1) are, and remain the property of Amphinol Corp. (2) must be returned upon request, and (3) are not to be used for the manufacture of any other product without those instructions being given by Amphinol Corp. The furnishing of these drawings and specifications for other data by Amphinol Corp., or to any other person to enforce for any purpose is not to be requested by implication or otherwise in any manner liberally, granting the user of these drawings, specifications, or other person to manufacture, use or any product, process or design, obtained by any other person in any way so related to or identified by said drawings, specifications, or other data. | REFERENCE |
| DRAWN
R. PERCY
CHECKED
H. HITTER
ENGINEER
E.S. HULL
APPROVED
K. GUELLER
D. FUSARD
MFG ENG | DATE
02-08-90
DATE
4-25-84
DATE
07-20-90
DATE
4-25-84
DATE
4-30-84 |
| TITLE
ADAPTOR
N PLUG
SMA JACK | Amphenol Corporation
RF/Microwave Operations
Donbury, Conn. USA 06810
SCALE: 8=1 |
| CODE ID
Z4868
R | DWG SIZE
901-2501-510
ISSUE
R |