

# Product Specifications



43211A

Butterfly Hanger for 1/2 in or 3/8 in coaxial cable and elliptical waveguide 180, 220, and 240



## CHARACTERISTICS

### Dimensions

---

Nominal Size	1/2 in
Compatible Diameter, maximum	16.256 mm   0.640 in
Compatible Diameter, minimum	10.414 mm   0.410 in
Height	31.75 mm   1.25 in
Length	40.64 mm   1.60 in
Width	38.10 mm   1.50 in

### Electrical Specifications

---

DTF Effect	0.1 dB
Return Loss Effect	0.1 dB

### General Specifications

---

Hanger Type	Standard butterfly hanger
Cables Per Hanger	1
Color	Silver
Material Type	Stainless steel
Package Quantity	10

### Mechanical Specifications

---

Axial Load Capability, minimum with no cable slippage	≥5 times cable weight
Corrosion Resistance, minimum with no degradation	≥500 hours in salt spray chamber
Mounting	3/8 in (M10) drilled cable ladder
Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
Vibration Survival	≥4 hours at resonant frequency

### Packed Dimensions

---

Height	14.8 cm   5.8 in
Length	9.0 cm   3.5 in
Shipping Weight	0.34 kg   0.75 lb
Width	10.6 cm   4.2 in

# Product Specifications

43211A



## Regulatory Compliance/Certifications

---

### Agency

RoHS 2002/95/EC  
China RoHS SJ/T 11364-2006  
ISO 9001:2008

### Classification

Compliant  
Below Maximum Concentration Value (MCV)  
Designed, manufactured and/or distributed under this quality management system

