

Product Specifications



SG158-12B2U

SureGround® Grounding Kit for 1-5/8 in coaxial cable



CHARACTERISTICS

Dimensions

Nominal Size	1-5/8 in
Bonding Conductor Length	1219.2 mm 48 in
Cable Jacketing Removal Length, maximum	38.1 mm 1 1/2 in
Cable Jacketing Removal Length, minimum	38.1 mm 1 1/2 in
Compatible Diameter, maximum	50.800 mm 2.000 in
Compatible Diameter, minimum	49.022 mm 1.930 in

Electrical Specifications

Current Handling	Tested to withstand 100,000 amps peak current surge
Current Handling Test Method	MIL-STD-1757
Grounding, Bonding and Shielding Test Method	MIL-STD-188-124A
Lightning Protection Test Method	IEC 1024-1

General Specifications

Cable Type	Corrugated Smoothwall
Grounding Kit Type	SureGround™ Grounding Kits
Brand	SureGround™
Color	Black
Bonding Conductor Material	Copper
Bonding Conductor Wire Size	6 gauge
Bonding Conductor Jacketing Material	PE
Grounding Strap Material	Tinned copper
Includes	Grounding kit Hardware Lug One roll of 2 in PVC tape One roll of 24 in butyl rubber tape
Locking Bail Material	Stainless steel
Lug Attachment	Field attached
Lug Type	Two-hole lug
Package Quantity	1
Rivet Material	Tinned copper
Weatherproofing Method	Butyl and electric tape

Product Specifications



SG158-12B2U

Mechanical Specifications

Blowing Rain Test Method	MIL-STD-810, Method 506
Corrosion Test Method	MIL-STD-1344, Method 1001
Freezing Rain/Icing Test Method	MIL-STD-810, Method 521
Humidity Test Method	MIL-STD-1344, Method 1002
Immersion Test Method	IEC 60529:2001, IP68
Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
Storage Temperature	-40 °C to +80 °C (-40 °F to +176 °F)
Thread Size	3/8 in
UV Resistance Test Method	MIL-STD-810, Method 505
Vibration Test Method	MIL-STD-202, Method 214

Packed Dimensions

Height	304.8 mm 12.0 in
Length	25.4 mm 1.0 in
Shipping Weight	0.90 kg 1.98 lb
Width	279.4 mm 11.0 in

Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system

INCLUDED PRODUCTS



9905-71
Black 2 in PVC Tape, 20 ft



42615-10
Butyl Rubber Tape, 24 in

* Footnotes

Grounding, Bonding and Shielding Test Method	Military Standard for Grounding, Bonding, and Shielding: Bond Resistance Requirement of a Maximum dc resistance of 0.001 ohm
Lightning Protection Test Method	Protection Against Lightning Electromagnetic Impulse, Table 1—Protection Level III-IV, 1995-02