



For more Information  
please call

1-800-Belden1



## General Description:

13 AWG stranded (7x21) .089" bare copper conductor, polyethylene insulation, bare copper braid shield (96% coverage), non-contaminating PVC jacket.

## Physical Characteristics (Overall)

### Conductor

#### AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (mm)
1	13	7x21	BC - Bare Copper	2.2606

Total Number of Conductors: 1

### Insulation

#### Insulation Material:

Insulation Material	Dia. (mm)
PE - Polyethylene	7.239

### Outer Shield

#### Outer Shield Material:

Type	Outer Shield Material	Coverage (%)
Braid	BC - Bare Copper	96

### Outer Jacket

#### Outer Jacket Material:

Outer Jacket Material
PVCNC - Polyvinyl Chloride Non-Contaminating

### Overall Cable

Overall Nominal Diameter: 10.287 mm

## Mechanical Characteristics (Overall)

Operating Temperature Range:	-40°C To +80°C
UL Temperature Rating:	60°C (UL AWM Style 1354)
Bulk Cable Weight:	154.773 Kg/Km
Max. Recommended Pulling Tension:	818.469 N
Min. Bend Radius/Minor Axis:	127 mm

## Applicable Specifications and Agency Compliance (Overall)

### Applicable Standards & Environmental Programs

NEC/(UL) Specification:	CMX
CEC/C(UL) Specification:	CMX
AWM Specification:	UL Style 1354 (30 V 60°C)
EU Directive 2011/65/EU (ROHS II):	Yes
EU CE Mark:	No
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes

EU RoHS Compliance Date (mm/dd/yyyy):	10/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Military Specification:	MIL-C-17, M17/163-00001
RG Type:	213/U

### Flame Test

UL Flame Test:	VW-1
----------------	------

### Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

## Electrical Characteristics (Overall)

### Nom. Characteristic Impedance:

Impedance (Ohm)

50

### Nom. Inductance:

Inductance (µH/m)

0.252637

### Nom. Capacitance Conductor to Shield:

Capacitance (pF/m)

101.055

### Nominal Velocity of Propagation:

VP (%)

66

### Nominal Delay:

Delay (ns/m)

5.05274

### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)

5.5777

### Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/km)

3.9372

### Nom. Attenuation:

Freq. (MHz) Attenuation (dB/100m)

1	0.88587
10	1.80455
50	4.2653
100	6.2339
200	8.8587
400	13.4521
700	21.3265
900	24.9356
1000	26.248
4000	70.5415

### Max. Power Rating:

Freq. (MHz) Rating (W)

1	7950
10	2761
50	1122
100	748

200	494
400	326
700	235
900	205
1000	194
4000	110

**Max. Operating Voltage - UL:**

Voltage	Description
30 V RMS	UL AWM Style 1354
300 V RMS	NEC

**Max. Operating Voltage - Non-UL:**

Voltage
3700 V RMS (MIL-SPEC)

**Misc. Information (Overall)**

**Notes (Overall)**

**Notes:** Non-SWR swept version of RG-213.

**Put Ups and Colors:**

Item #	Putup	Ship Weight	Color	Notes	Item Desc
8267 0101000	305 MT	53.071 KG	BLACK	C	M17-163-00001 COAX
8267 010500	152 MT	26.989 KG	BLACK	C	M17-163-00001 COAX

**Notes:**

C = CRATE REEL PUT-UP.

Revision Number: 2    Revision Date: 03-30-2012

© 2013 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.