



## Andrew Solutions FSJ4RK-50B

**FSJ4-50B, HELIAX® Superflexible Foam Coaxial Cable, corrugated copper, 1/2 in, black non-halogenated, fire retardant polyolefin jacket**

### Construction Materials

Jacket Material	Non-halogenated, fire retardant polyolefin
Outer Conductor Material	Corrugated copper
Dielectric Material	Foam PE
Flexibility	Superflexible
Inner Conductor Material	Copper-clad aluminum wire
Jacket Color	Black

### Dimensions

Nominal Size	1/2 in
Cable Weight	0.16 lb/ft   0.24 kg/m
Diameter Over Dielectric	8.890 mm   0.350 in
Diameter Over Jacket	13.462 mm   0.530 in
Inner Conductor OD	3.5560 mm   0.1400 in
Outer Conductor OD	12.192 mm   0.480 in

### Electrical Specifications

Cable Impedance	50 ohm ±1 ohm
Capacitance	25.2 pF/ft   82.7 pF/m
dc Resistance, Inner Conductor	0.820 ohms/kft   2.690 ohms/km
dc Resistance, Outer Conductor	1.000 ohms/kft   3.281 ohms/km
dc Test Voltage	2500 V
Inductance	0.207 µH/m   0.063 µH/ft
Insulation Resistance	100000 Mohms•km
Jacket Spark Test Voltage (rms)	4000 V
Operating Frequency Band	1 – 10200 MHz
Peak Power	15.6 kW
Pulse Reflection	1%
Velocity	81%

### Environmental Specifications

Installation Temperature	-25 °C to +60 °C (-13 °F to +140 °F)
Operating Temperature	-30 °C to +80 °C (-22 °F to +176 °F)
Storage Temperature	-30 °C to +80 °C (-22 °F to +176 °F)

### General Specifications

FSJ4RK-50B



---

Brand HELIAX®

## Mechanical Specifications

---

Bending Moment	2.7 N-m   2.0 ft lb
Fire Retardancy Test Method	UL 1666/CATVR/CMR
Flat Plate Crush Strength	110.0 lb/in   2.0 kg/mm
Minimum Bend Radius, Multiple Bends	31.75 mm   1.25 in
Minimum Bend Radius, Single Bend	33.02 mm   1.30 in
Number of Bends, minimum	30
Number of Bends, typical	50
Smoke Index Test Method	IEC 61034
Tensile Strength	79 kg   175 lb
Toxicity Index Test Method	IEC 60754-1   IEC 60754-2

## Note

---

Performance Note Values typical, unless otherwise stated

## Standard Conditions

---

Attenuation, Ambient Temperature	20 °C   68 °F
Average Power, Ambient Temperature	40 °C   104 °F
Average Power, Inner Conductor Temperature	100 °C   212 °F

## Attenuation

Frequency (MHz)	Attenuation (dB/100 m)	Attenuation (dB/100 ft)	Average Power (kW)
0.5	0.231	0.07	15.60
1	0.327	0.1	15.60
1.5	0.401	0.122	15.60
2	0.463	0.141	15.60
10	1.044	0.318	10.12
20	1.485	0.453	7.11
30	1.828	0.557	5.78
50	2.377	0.724	4.44
88	3.187	0.971	3.32
100	3.406	1.038	3.10
108	3.546	1.081	2.98
150	4.214	1.285	2.51
174	4.558	1.389	2.32
200	4.908	1.496	2.15
300	6.095	1.858	1.73
400	7.121	2.17	1.48
450	7.592	2.314	1.39
500	8.042	2.451	1.31
512	8.148	2.483	1.30
600	8.891	2.71	1.19
700	9.683	2.951	1.09
800	10.431	3.179	1.01
824	10.605	3.232	1.00
894	11.101	3.383	0.95
960	11.555	3.522	0.91
1000	11.824	3.604	0.89
1250	13.423	4.091	0.79
1500	14.906	4.543	0.71
1700	16.027	4.885	0.66
1800	16.57	5.05	0.64
2000	17.624	5.371	0.60
2100	18.137	5.528	0.58
2200	18.641	5.682	0.57
2300	19.138	5.833	0.55
2500	20.11	6.129	0.53
2700	21.056	6.418	0.50
3000	22.432	6.837	0.47
3400	24.198	7.375	0.44
3700	25.478	7.765	0.41
4000	26.727	8.146	0.40
5000	30.693	9.355	0.34
6000	34.427	10.493	0.31
8000	41.403	12.619	0.26
8800	44.054	13.427	0.24
10000	47.914	14.604	0.22

\* Values typical, guaranteed within 5%

## Regulatory Compliance/Certifications

Agency	Classification
UL/ETL Certification	CATVR/CMR
RoHS 2002/95/EC	Compliant

# Product Specifications

COMMSCOPE®

FSJ4RK-50B



China RoHS SJ/T 11364-2006  
ISO 9001:2008

Below Maximum Concentration Value (MCV)  
Designed, manufactured and/or distributed under this quality management system

