

## Coaxial Cable Connector 11\_SMA-50-4-53/139\_N

### Description

Straight cable plug

Interface standards

IEC 60169-15\_MIL-STD-348A/310\_CECC 22110



### Technical Data

#### Electrical Data

Impedance	50 Ω
Interface frequency max.	18 GHz

#### Mechanical Data

Centre contact	plugged
Outer contact	crimped
Weight	0.0071 kg

#### Environmental Data

Operating temperature	-65 °C to 125 °C
2011/65/EU, RoHS	compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Stainless Steel	Passivated (Plating)
Gasket	VMQ (Silicone rubber)	
Crimp ferrule	Copper	SUCOPLATE (R) Plating

### Related Documents

Outline drawing	DOU-00006903
Assembly instruction	DOC-0000179057

### Ordering Information

Single package	11_SMA-50-4-53/139_NE
----------------	-----------------------

### Additional Information

Suitable cables	S_04272_B, S_04262B-01
-----------------	------------------------

### Remarks

Use torque wrench 74\_Z-0-0-79 (0.45Nm)