

Product Specifications



AVA5-50

AVA5-50, HELIAX® Andrew Virtual Air™ Coaxial Cable, corrugated copper, 7/8 in, black PE jacket



CHARACTERISTICS

Construction Materials

Jacket Material	PE
Outer Conductor Material	Corrugated copper
Dielectric Material	Foam PE
Flexibility	Standard
Inner Conductor Material	Copper tube
Jacket Color	Black

Dimensions

Nominal Size	7/8 in
Cable Weight	0.30 lb/ft 0.45 kg/m
Diameter Over Dielectric	24.130 mm 0.950 in
Diameter Over Jacket	27.940 mm 1.100 in
Inner Conductor OD	9.398 mm 0.370 in
Outer Conductor OD	25.400 mm 1.000 in

Electrical Specifications

Cable Impedance	50 ohm $\pm$ 1 ohm
Capacitance	22 pF/ft 73 pF/m
dc Resistance, Inner Conductor	0.410 ohms/kft 1.435 ohms/km
dc Resistance, Outer Conductor	0.340 ohms/kft 1.116 ohms/km
dc Test Voltage	6000 V
Inductance	0.184 μ H/m 0.056 μ H/ft
Insulation Resistance	100000 MOhm
Jacket Spark Test Voltage (rms)	8000 V
Operating Frequency Band	1 – 5000 MHz
Peak Power	91.0 kW
Pulse Reflection	0.5%
Velocity	91%

Environmental Specifications

Product Specifications

AVA5-50



Installation Temperature	-40 °C to +60 °C (-40 °F to +140 °F)
Operating Temperature	-55 °C to +85 °C (-67 °F to +185 °F)
Storage Temperature	-70 °C to +85 °C (-94 °F to +185 °F)

General Specifications

Brand	HELIAX®
-------	---------

Mechanical Specifications

Bending Moment	19.0 N-m 14.0 ft lb
Flat Plate Crush Strength	75.0 lb/in 1.3 kg/mm
Minimum Bend Radius, Multiple Bends	254.00 mm 10.00 in
Minimum Bend Radius, Single Bend	127.00 mm 5.00 in
Number of Bends, minimum	15
Number of Bends, typical	30
Tensile Strength	159 kg 350 lb

Standard Conditions

Attenuation, Ambient Temperature	20 °C 68 °F
Average Power, Ambient Temperature	40 °C 104 °F
Average Power, Inner Conductor Temperature	100 °C 212 °F

Return Loss

Frequency Band	VSWR	Return Loss (dB)
806–960 MHz	1.13	24.30
1700–2000 MHz	1.13	-24.30

Attenuation

Frequency (MHz)	Attenuation (dB/100 ft)	Attenuation (dB/100 m)	Average Power (kW)
0.5	0.023	0.076	91.00
1	0.033	0.108	77.97
1.5	0.04	0.132	63.61
2	0.046	0.153	55.06
10	0.105	0.343	24.48
20	0.149	0.487	17.23
30	0.183	0.599	14.02
50	0.237	0.777	10.81
88	0.317	1.039	8.08
100	0.338	1.11	7.57
108	0.352	1.155	7.27
150	0.417	1.369	6.14
174	0.451	1.479	5.68
200	0.485	1.591	5.28
300	0.6	1.968	4.27
400	0.698	2.292	3.67
450	0.744	2.44	3.44
500	0.787	2.581	3.25
512	0.797	2.614	3.21
600	0.868	2.846	2.95
700	0.943	3.093	2.72

Product Specifications

AVA5-50



800	1.014	3.325	2.53
824	1.03	3.379	2.49
894	1.077	3.533	2.38
960	1.119	3.673	2.29
1000	1.145	3.756	2.24
1250	1.294	4.247	1.98
1500	1.432	4.7	1.79
1700	1.536	5.04	1.67
1800	1.586	5.205	1.61
2000	1.683	5.523	1.52
2100	1.731	5.678	1.48
2200	1.777	5.83	1.44
2300	1.822	5.979	1.40
2500	1.911	6.27	1.34
2700	1.997	6.553	1.28
3000	2.122	6.963	1.21
3400	2.282	7.487	1.12
4000	2.51	8.234	1.02
5000	2.864	9.396	0.89

Regulatory Compliance/Certifications

Agency

RoHS 2002/95/EC

China RoHS SJ/T 11364-2006

Classification

Compliant

Below Maximum Concentration Value (MCV)

